



PROTECTA-LINE

- Protecta-Line® encompasses a fully integrated system of pipe and fittings: Protecta-Line® Mechanical Compression Fittings, Protecta-Line® Stop Cocks, Protecta-Line® Self Tapping Ferrule Off-Takes and Protecta-Line® Fluid Compression Fittings
- The double bonded construction incorporates an impermeable metal barrier wrapped onto a standard central core pipe of Excel® (PE100) or PE80 conforming to BS EN 12201, BS 6572 or WIS 4-32-17
- No contact between the pipe's protective aluminium layer and drinking water
- Protecta-Line® pipe is from 25mm to 63mm in SDR11 PE80 and from 90mm to 180mm in SDR 11 and SDR17 PE100. Available in 6m and 12m sticks, 50m and 100m coils, depending on diameter
- 6m straight lengths are available at sizes 63mm to 180mm and 12m straight lengths are available at size 125mm and above
- All sizes are available in 50m coils; 100m coils are available at size 63mm and above. 63mm Protecta-Line® pipe is also available in 25m coils
- Protecta-Line® Mechanical Compression Fittings from 25mm to 63mm including Couplers, Reducers, Transition Fittings, Equal Tees and 90° Elbows
- Protecta-Line® Stop Cocks at 25mm and 32mm
- Protecta-Line® Self Tapping Ferrule Off-Takes in main sizes 63mm to 180mm, with 25mm and 32mm outlets
- Protecta-Line® Fluid Compression Fittings from 63mm to 180mm including Couplers, Reducers, 90° Elbows, 45° Elbows, Equal Tees, Flanged Branch Tees and Stub Flanges
- Protecta-Line®'s multi-layer composite pipe prevents potential tainting caused by through-wall permeation in contaminated land
- Protecta-Line® is lightweight, flexible and easy to install just like conventional PE pipe
- Protecta-Line® is the most complete system of pipe and fittings available which are compliant with WIS 4-32-19



Tel: 0871 2000997 Fax: 0871 2000998 e-mail: sales@egsutilities.co.uk
Tel: 0871 2000997 Fax: 0871 2000998 e-mail: sales@egsutilities.co.uk